

WEIGH-TRONIX

WI-125 LED Indicator with Keypad and LED Display

- Washdown safe
- Numeric keypad
- Easy operation
- Fast-reading LED display

Enclosed in a stainless steel NEMA 4X case, the WI-125 LED Indicator will serve you effectively in wet or dry environments. And its crisp, easy-reading LED display will speed any weighing process.



WI-125 LED Indicator with Keypad and LED Display

Features and benefits

Six function keys— No confusing functions. Train operators in minutes

LED display— Bright, crisp, fast-reading. Speeds weighing process and reduces operator error.

NEMA 4X washdown— Stainless steel enclosure provides corrosion and washdown resistance to rough indoor and outdoor use.

Numeric keypad— Makes tare entry more flexible. Enter known weights from the keypad, or use the TARE key to enter container weights.

RS-232 serial port— Provides link with printers and computers.

Print formatting— Customize your printout with company name, message, character size and location, etc. right from the front panel.

Heavy-duty swivel mounting stand— Adjust the display quickly to the best sight line.

RFI protection— Provides stable weight readings in environments with moderately high levels of RFI radiation.

Option

**Time and date
RS-485 serial port**

Specifications

Power:

115 volts AC/230 volts AC, 50/60 Hz single phase

Display:

Eight .6-inch high LED digits with LED annunciators

Display rate:

Configurable to 1, 2, or 5 times per second

Display averaging: One to ten display periods

A to D conversion rate: 60 times per second

Internal resolution:

884,736 counts at 3 mV/V

294,912 counts at 1 mV/V

Increments:

0.0001 to 20,000 programmable to any division size between these limits.

Controls:

GROSS/NET, TARE, ZERO, PRINT, UNITS, MENU, Keypad (0-9)

Annunciators:

Gross, net, center of zero, print, lb and kg

Excitation: 10 VDC

Load cells:

Drives up to 12 350-ohm Weigh Bars® or load cells

Agencies:

NTEP, pending

Canadian Weights and Measures, pending

Analog range: -0.14 to +3.5 mV/V

Operating temperature:

-10 to 40° C (14 to 104° F)

10 to 90% relative humidity

Shipping weight: 6.5 lb (2.9 kg)

Warranty: Two-year limited warranty applies.

Weigh-Tronix, Inc.

1000 Armstrong Drive

Fairmont, MN 56031 USA

Telephone +1 507-238-4461

Facsimile +1 507-238-4195

e-mail: industrial@weigh-tronix.com

www.weigh-tronix.com

Weigh-Tronix Canada, ULC

217 Brunswick Blvd.

Pointe Claire, Quebec H9R 4R7 Canada

Telephone +1 514-695-0380

Facsimile +1 514-695-6820



WEIGH-TRONIX

Weighing Products & Systems